

AN EXTENDED LIFETIME MEASURE FOR TELECOMMUNICATION NETWORK

ZARI DZALILOV, IRADJ OUVEYSI AND ALEXANDER RUBINOV

Centre for Informatics and Applied Optimization
School of Information Technology and Mathematical Sciences
University of Ballarat, Victoria 3353, Australia

(Communicated by Kok Lay Teo)

ABSTRACT. A new measure for network performance evaluation called topology lifetime was introduced in [4, 5]. This measure is based on the notion of unexpected traffic growth and can be used for comparison of topologies. We discuss some advantages and disadvantages of the approach of [4] and suggest some modifications to this approach. In particular we discuss how to evaluate the influence of a subgraph to the lifetime measure and introduce the notion of the order of a path. This notion is useful if we consider a possible extension to the set of working paths in order to support the traffic for the time that is needed for installation of new facilities.

1. Introduction. The ability of a telecommunication network to support the expected growth in demand is an important characteristic of the network (see, for example, [3, 10, 11]). However, it is not enough to only consider the expected growth: an unexpected growth can often occur due to some technological innovations and the increasing popularity of the Internet (see [4] for a corresponding discussion). A quantitative measure for telecommunications topology design was suggested by N. Maxemchuk, I. Ouveysi and M. Zukerman in [4]. This measure was called topology lifetime. Possible unexpected changes in the load have been taken into account in [4]. Note that the topology lifetime measure depends not only on topology but also on the set of working paths. In the current paper we discuss some advantages and disadvantages of the approach proposed in [4, 5] and its possible modifications. Two other topics are also discussed in this paper. The first is the notion of the order of a path (a special measure for comparison of paths). We need such a measure for the evaluation of paths that can be added to the set of working paths, if it is necessary to support the traffic when large unexpected changes in load arise. The second topic is the evaluation of the lifetime measure of a sub-network of the given network. To this end, we use a modification of certain ideas of [1, 2] for this purpose. The focus of the present paper is mainly theoretical and we leave for further study the application of our proposed approaches to real networks.

2000 *Mathematics Subject Classification.* Primary: 90C05 ,90C90 ; Secondary:90C35.

Key words and phrases. Linear programming, Network life-time analysis, Network management and optimisation.

2. Preliminaries. Consider a network defined by the graph $G = \langle V, E \rangle$ with the set V of vertices (nodes) and the set E of edges (arcs, links). Our approach is suitable for both directed and undirected topologies. For the sake of definiteness we will consider undirected topologies, so we consider G as a non-oriented graph. Assume that capacities $c_{k,l}$ ($(k,l) \in E$) are given. Since we consider an undirected topology, it follows that $c_{k,l} = c_{l,k}$. Recall that a path $p = (v, i, \dots, j, v')$ between $v, v' \in V$ is a sequence of links $(v, i), (i, k), \dots, (j, v')$, which does not contain cycles. The number of links in p is called the length of p . Since the graph G is non-oriented, a path (v, i, \dots, j, v') coincides with the path (v', j, \dots, i, v) .

The set of all paths generated by G is denoted by $P(G)$. We take into account only a small subset $P^*(G)$ of *working paths*. We use the following notation:

$P_{k,l}^*(G)$ is the set of paths from $P^*(G)$, which contain the link (k, l) ;

$P^*(i, j; G)$ is the set of paths from $P^*(G)$ with the end-points i and j .

Denote by x_p the amount of flow sent through a working path p . The totality $(x_p)_{p \in P^*(G)}$ of all flows is called a traffic generated by set of working paths $P^*(G)$. We will consider only feasible traffics $(x_p)_{p \in P^*(G)}$. Feasibility means that $x_p \geq 0$ for all $p \in P^*(G)$ and

1) the total flow transmitted through each link $(k, l) \in E$ does not exceed the capacity $c_{k,l}$ of this link:

$$\sum_{p \in P_{k,l}^*(G)} x_p \leq c_{k,l}, \quad (k, l) \in E.$$

2) the traffic requirement constraints are satisfied.

In order to explain 2) we assume that the present traffic demand is represented by a finite collection \mathcal{T} of traffic matrices T . Each $T \in \mathcal{T}$ describes the traffic demand between all OD pairs at a certain time period. Let $T = (t_{ij})$. Then t_{ij} is the traffic demand from node i to node j at the time period under consideration. Since we consider undirected traffic, we have $t_{ij} = t_{ji}$. Clearly $t_{ii} = 0$ for all i . Traffic $(x_p)_{p \in P^*(G)}$ satisfies traffic requirement constraints if

$$\sum_{p \in P^*(i,j;G)} x_p \geq t_{i,j}$$

for all $i, j \in V, i \neq j$ and for all $T = (t_{ij}) \in \mathcal{T}$.

3. Feasibility and growth factor of traffic matrix. Consider a traffic matrix $T \in \mathcal{T} : T = (t_{ij})$. Let $P^*(G)$ be the set of working paths. Consider the system of linear inequalities:

$$\sum_{p \in P^*(i,j;G)} x_p \geq t_{i,j}, \quad i, j \in V, i \neq j \tag{1}$$

$$\sum_{p \in P_{k,l}^*(G)} x_p \leq c_{k,l}, \quad (k, l) \in E \tag{2}$$

$$x_p \geq 0, \quad p \in P^*(G).$$

If this system has a solution, the matrix T is called a feasible matrix. (Sometimes the different definition of feasibility is used, where the inequality in (1) is replaced with the equality. However the form of feasibility which we use is more natural.)

The growth factor $\psi_*(T)$ of the traffic matrix T (see [4]), is the largest number ψ such that the traffic $\psi T = (\psi t_{i,j})$ is feasible. (The authors of [4] used the

definition of feasibility with equalities in (1.) Thus $\psi_*(T)$ is a solution of the linear programming problem:

$$\text{maximize } \psi \text{ subject to } ((x_p)_{p \in P^*}, \psi) \in X(T)$$

where $X(T)$ consists of all the collections $((x_p)_{p \in P^*}, \psi)$ such that $\psi \geq 0$, (2) holds and

$$\sum_{p \in P^*(i,j)} x_p = \psi t_{i,j}, \quad i, j \in V, i \neq j \quad (3)$$

The number $\psi_*(T)$ indicates the biggest possible uniform growth of the traffic T . The number $\psi_*(\mathcal{T}) = \min\{\psi_*(T) : T \in \mathcal{T}\}$ is the biggest possible uniform growth of the traffic represented by the collection \mathcal{T} .

The definition of the growth factor is based on a multiplicative approach to traffic extension, since we consider the products of the form $\psi \cdot t_{i,j}$. One of possible approaches to the lifetime measure is to consider an optimization problem with constraints (3) where not only x_p and ψ but also t_{ij} are variable. Such a problem arises if we want to estimate the worst performance with the respect to a set of matrices T . Unfortunately constraints (3) are bilinear with respect to the totality $\psi, t_{i,j}$. Currently problems of high dimension with such constraints can not be numerically solved.

4. Unexpected traffic growth. An unexpected growth of traffic was discussed in [4] separately for OD pairs and for nodes. First we consider OD pairs. Let T be a traffic matrix and (i, j) be an OD pair. Assume that the traffic between i and j increases by U . Then it is suggested in [4] to consider a new traffic matrix $T'(U) \equiv T'(i, j)(U)$ with

$$t'_{i,j} = (1 + U)t_{i,j}, \quad t'_{j,i} = t'_{i,j}$$

and

$$t'_{i',j'} = r_{i,j} t_{i',j'}, \quad (i', j') \neq (i, j), (i', j') \neq (j, i).$$

Here $r_{i,j}$ is the coefficient which provides the equality

$$\sum_{p,q \in V} t'_{p,q} = \sum_{p,q \in V} t_{p,q}.$$

Thus T' describes a shift in load without growth. A family of matrix $T'(i, j)$ corresponding to each OD pair (i, j) is considered in [4]. In other words it is assumed that an unexpected growth of traffic can occur only for one pair of OD, and this pair is unknown. The growth factor $\psi_*(T'(i, j))$ is then calculated for each matrix $T'(i, j)$ and the number $\Psi_*(T, U) = \min_{(i,j) \in V} \psi_*(T'(i, j))$ is considered as a parameter that characterizes an unexpected traffic growth U corresponding to the matrix T . If a collection \mathcal{T} of traffic matrices T is given, then we need to apply the described procedure for each matrix T . Then we obtain a new collection of traffic matrices, which consists of all matrices $T'(i, j)$ for all $T \in \mathcal{T}$ and all $i, j \in V, i \neq j$. The number $\min\{\Psi_*(T, U) : T \in \mathcal{T}\}$ characterizes an unexpected traffic growth U corresponding to collection \mathcal{T} .

The similar approach was suggested in [4] for the case when single nodes become active. For a particular node j we consider a matrix $\tilde{T} \equiv T(j)$ with

$$\tilde{t}_{ij} = \tilde{t}_{ji} = (1 + U)t_{ij}, \quad i \neq j$$

and

$$\tilde{t}_{ij'} = r_j t_{ij'}, \quad j' \neq j, i \neq j',$$

where r_j is the coefficient which provides the equality

$$\sum_{p,q \in V} \tilde{t}_{pq} = \sum_{p,q \in V} t_{pq}.$$

The described approach is very interesting and can be used for comparison of different topologies. However, this approach is based on strong enough hypotheses. We only comment on the case of OD pairs. The construction of matrices $T'(i, j)$ is based on the assumption that the uniform redistribution of the amount $2Ut_{i,j}$ is carried out between all OD (i', j') with $(i', j') \neq (i, j)$ and $(i', j') \neq (j, i)$. This uniformity does not always hold in real world networks. The assumption that an unexpected growth can occur only for one pair of OD is also not valid in many cases. The following situation should be also taken into account. Assume that unexpected growth occurs for a pair (i, j) at the end of the first year. This leads to a change of the collection \mathcal{T} of traffic matrices. So we have a different collection \mathcal{T}' of traffic matrices in the second year and cannot use the results obtained for the collection \mathcal{T} . This means that we need to recalculate the lifetime measure in the second year. However, the proposed lifetime measure is used for the evaluation of topology design so we should not recalculate it each year. It is therefore important to consider a modification to the construction from [4] that is not based on the two mentioned assumptions.

We suggest the consideration of the additive approach rather than the multiplicative approach for the definition of the lifetime measure.

Let U be a positive number that indicates the total amount of an unexpected traffic growth for the required period of time. Consider the system of linear inequalities

$$\sum_{p \in P^*(i,j;G)} x_p \geq U + t_{i,j}, \quad i, j \in V, i \neq j \quad (4)$$

$$\sum_{p \in P_{k,l}^*(G)} x_p \leq c_{k,l}, \quad (k, l) \in E \quad (5)$$

$$x_p \geq 0, \quad p \in P^*(G). \quad (6)$$

Composing (4) we suppose that unexpected traffic growth U can happen in many arcs and nodes simultaneously. This situation is more realistic than that suggested in [4], where only a single node (or a single arc) becomes more active. Indeed, the increase of activity in a node can lead to the increase of activity in many different nodes. This may cause some network elements to be congested which will require performing some dynamic rerouting [6, 7, 8, 9, 13] of the flows [12] in the network.

One of the main reasons for unexpected growth is the Internet. A server farm, which provides a popular service can suddenly appear and then the load to the corresponding part of network increases. However, the same reasons that lead to appearance of this farm will also lead to appearance of different farms in different parts of network in different years of the period of time τ under consideration. So it is important to take into account many nodes simultaneously. Note that U is an upper bound for the total unexpected increase of load for the time period τ for each OD pair (i, j) .

The suggested approach is pessimistic, because we assume a worst case scenario (unexpected increase in all nodes simultaneously). We are forced to take into account arbitrary unexpected traffic growth if we do not have any forecasts. Usually if some forecasts are known, they can narrow the area of unexpected traffic growth.

We can either exclude unexpected growth for some links or consider them with coefficients, less than one. This means that instead of (4) we can consider the following:

$$\sum_{p \in P^*(i,j;G)} x_p \geq \alpha_{ij}U + t_{i,j}, \quad i, j \in V, i \neq j \quad (7)$$

where $0 \leq \alpha_{ij} \leq 1$. For the sake of simplicity we assume that $\alpha_{ij} = 1$ for all i, j . Note that we do not need to consider links and nodes separately.

In order to check that the system (4)-(6) is feasible it is enough to solve a linear programming problem with an arbitrary linear objective function f and constraints (4) - (6). The most appropriate objective function in this situation is the total traffic:

$$f(X) = \sum_{p \in P^*(G)} x_p,$$

where $X = (x_p)_{p \in P^*(G)}$. Thus we shall consider the following linear programming problem LP(T,U):

$$\text{maximize} \quad \sum_{p \in P^*(G)} x_p. \quad (8)$$

subject to constraints (4)-(6). The system (4)-(6) is feasible if and only if the maximum in (8) is finite. The value of this maximum is denoted by $\lambda(T, U)$. If the system (4)-(6) is unfeasible then the maximum in (8) (that is, the maximum over the empty set) is equal to $-\infty$, so $\lambda(T, U) = -\infty$. It is easy to check that the $\lambda(T, U)$ is a decreasing and concave function of U for each T .

The number $\lambda(T, U)$ indicates the greatest possible total traffic that can provide (4) and (5) for a given matrix T . We consider this number as a certain lifetime measure of a topology under consideration for the traffic matrix T . Let a collection \mathcal{T} of traffic matrices T be given. Assume that systems (4)-(6) are feasible for each $T \in \mathcal{T}$, then the unexpected traffic growth $\lambda(\mathcal{T}, U)$ corresponding to \mathcal{T} can be calculated as the minimum of $\lambda(T, U)$ over the set \mathcal{T} . We consider $\lambda(\mathcal{T}, U)$ as a lifetime measure for the given topology, the given collection \mathcal{T} and the given set $P^*(G)$ of working paths.

Thus we suggest the use of a simple one-step procedure for the definition of lifetime measure instead of consecutive two-step procedure from [4].

5. Extensions of the set of working paths. Let U be a number such that the problem LP(T,U') is feasible for $U' < U$ and LP(T,U') is unfeasible for $U' > U$. Assume that the problem LP(T,U) is feasible and let $((x_p)_{p \in P^*(G)})$ be its solution. If all the inequalities (4) hold in the strong sense then there exists $U' > U$ such that LP(T,U') is also feasible, which contradicts the definition of U . Hence, (4) holds as the equality for at least one link. Links $(k, l) \in E$, where the equality holds, indicate the bottleneck that does not permit an unexpected load greater than U .

If the load distribution that occurs due to unexpected load growth, exceeds the network possibilities then new facilities should be installed. In order to support the traffic for the time that is needed for installation of these facilities, the set $P^*(G)$ of working paths needs to be extended. We can attract new paths that do not contain links (k, l) , where the inequality in (2) holds as the equality. It is easy to find examples, where even a few such paths allow us to significantly increase the capacity to handle an unexpected load.

Clearly it is beneficial to use only fairly short paths in the telecommunication networks. Usually the shortest path or first k shortest paths with $k > 1$ are considered. It is more convenient to introduce a special notion of the order of a path and then only consider the paths with small enough orders. Using this notion we can analyze and compare the potential useful paths for different ODs and say for example, that it is beneficial to include new working paths only for OD pairs $(i_1, j_1), (i_2, j_2), (i_3, j_3)$ and consider first k shortest paths with $k = 1$ ($k = 2, k = 3$, respectively) for (i_1, j_1) ($(i_2, j_2), (i_3, j_3)$, respectively.)

6. Order of a path. Different notions of the order of a path can be introduced for estimating its quality. We consider three different notions of the order.

Let $v, v' \in V, v \neq v'$. The length of the shortest path with the end-nodes v and v' is denoted by $\lambda(v, v')$. Consider now a path $p = (v, \dots, v_i, \dots, v')$ with the same end-nodes and the length $\lambda(p)$. The number $\sigma_1(p) = \frac{\lambda(p)}{\lambda(v, v')}$ indicates how many superfluous links are contained in the path p . Note that $\sigma_1(p) \geq 1$. If $\sigma_1(p)$ is a large number then the path p contains many superfluous links. We can consider $\sigma_1(p)$ as the order of the path p .

The order $\sigma_1(p)$ is not suitable for the description of a situation, where only a certain part of the path contains superfluous links.

Example 6.1. Consider a path $p = (v_1, \dots, v_t, v_{t+1}, \dots, v_{t+s})$, where (v_1, \dots, v_t) is the shortest path between v_1 and v_t and there is link $l_{v_t, v_{t+s}}$, such that the shortest path between v_1 and v_{t+s} is $(v_1, \dots, v_t, v_{t+s})$. Then $\lambda(v_1, v_{t+s}) = t + 1$ and $\lambda(p) = t + s$ so $\sigma_1(p) = \frac{t+s}{t+1}$. Assume that s is fixed. If t is large enough then $\sigma_1(p)$ can be closed to 1, so accordingly, with respect to the factor σ_1 , the whole path p is good enough. However the sub-path (v_t, \dots, v_{t+s}) contains many superfluous links.

In order to reflect the influence of sub-paths to the quality of a path we can use the following construction. Consider a path $p = (v_0, v_1, \dots, v_{t-1}, v_t)$ and all sub-paths $p_{i,j} = (v_i, \dots, v_j)$ of this path. Let

$$\sigma_2(p) = \max_{i=0, \dots, k-1, i < j \leq t} \sigma_1(p_{i,j})$$

The number $\sigma_2(p)$ can be considered as another order of a path p . This order indicates the quality of the worst sub-path of this path. If this number is large then the path contains a sub-path with relatively large amount of superfluous links. In contrast with $\sigma_1(p)$, the number $\sigma_2(p)$ does not reflect the quality of the whole path. We can consider one of the numbers $\sigma_1(p), \sigma_2(p)$ or both of them for estimation of the quality of a path. Sometimes it is convenient to consider a combination of orders $\sigma_1(p)$ and $\sigma_2(p)$. A number

$$\sigma(p) = \frac{1}{2}(\sigma_1(p) + \sigma_2(p))$$

also can be considered as an order of the path p , which reflects the influence of a path itself and its sub-paths. We use this characteristic as the order. The order of a path is a convenient tool for comparison of different paths of the same length.

In the same manner we can define the order of a path in terms of the cost metric. It is easy to find examples where k -shortest paths between different OD pairs with the same k have different orders. In order to increase the growth factor, we can use some additional working paths with the small order σ .

7. Using forecast of growth of population. In order to have a more precise lifetime measure we need to use forecasts of growth of population and migrations flows. Usually such forecasts are known. We can assume that traffic between two nodes is proportional to the population of these nodes with a certain coefficient of proportionality γ which depends on different issues, in particular, on the rate of migration. Assume the a forecast suggests that the set of nodes V can be presented as the union of two disjoint sets V' and V'' : $V = V' \cup V''$. Assume that the population of nodes $v' \in V'$ will grow and the population of nodes $v'' \in V''$ will remain the same. Let u be the rate of growth of population at cities $i \in V'$ (We assume for the sake of simplicity that both u and the coefficient of proportionality γ do not depend on a node $i \in V'$.) Let \mathcal{T} be the set of current traffic matrices of $T = (t_{ij})$. Then a new traffic matrix $S_T(u)$ has entries s_{ij} where

$$\begin{aligned} s_{ij} &= \gamma^2(1+u)^2 t_{ij}, & i, j \in V' \\ s_{ij} &= \gamma(1+u) t_{ij}, & \begin{array}{l} i \in V', j \in V'' \\ i \in V'', j \in V' \end{array} \\ s_{ij} &= t_{ij}, & i, j \in V''. \end{aligned}$$

The set of matrices $\mathcal{S} = \{S_T(u) : T \in \mathcal{T}\}$ should be considered instead of \mathcal{T} for the calculation of the lifetime measure in the situation under consideration.

8. Using subgraphs. Different parts of the network have a different influence on the lifetime measure. Thus we need to consider the developed approaches not only for a given graph G but also for some of its subgraphs G' . In order to do this we need to determine the restriction of the traffic matrices T to a subgraph G' . The following definition is useful. A node $i \in V'$ is called an *outer node* for G' if there are links $(k, i) \in E$ with $k \notin V'$ and (i, j) with $j \in V'$.

Let $G' = \langle V', E' \rangle$ be a subgraph of G . Denote by V'' the complement to V' : $V'' = V \setminus V'$. We now classify all paths from $P^*(G)$ with respect to G' , namely we consider three classes of paths.

1) Paths p , which do not go through G' . This means that p does not contain links from E' . Note that some nodes of p can belong to V' , in such a case these are outer nodes of V' .

2) Paths p , which go through G' once. We say that a path p goes through G' once if p has the form

$$p = (v, \dots, i, \dots, j, \dots, u), \quad (9)$$

where $i, j \in V'$, $i \neq j$ and the path $p' = (i, \dots, j)$ is located in G' (the latter means that p' consists of links, which belong to E'). It is possible that $v = i$ and/or $j = u$. If $v \neq i$, then i is an outer node and the path (m, \dots, i) does not go through G' ; if $j \neq u$ then j is an outer node and (j, \dots, u) does not go through G' . If $v = i$ and $j = u$ then p is a path with the end-nodes i and v , which is located in G' . Thus an arbitrary path, which is located in G , is going through G' once.

3) Paths p , which go through G' more than once. This means that p contains more than one piece of the form $(i_\alpha, \dots, j_\alpha)$ with $i_\alpha \neq j_\alpha$, which is located in G' .

The analysis of paths, which go through G' more than once is difficult. The simplest way to handle these paths is to divide them into parts which go through G' once and examine these parts separately. Thus we can assume that the set $P^*(G)$ contains only paths that either do not go through G' or go through G' once. We use the following notation:

$P_{G'}^*(G)$ is the set of all working paths $p \in P^*(G)$ going through G' once.

$P_{G'}^*(i, j; G')$ is the set of all working paths of the form (9) with fixed $i, j \in V'$.

If nodes $i, j \in V'$ are not outer nodes of G' then $P_{G'}(i, j; G')$ coincides with the set $P(i, j; G')$ of all paths of G' with the end-nodes i and j .

Let U be a size of an unexpected growth in traffic and let $(\bar{x}_p)_{p \in P^*}$ be the set of paths such that $((\bar{x}_p)_{p \in P^*(G)})$ is a solution of problem LP(T,U). Let $G' = \langle V', E' \rangle$ be a subgraph of the graph G and let $i, j \in V'$, $i \neq j$. Consider a total flow y_{ij} , which should be transmitted from the node i to the node j through paths from $P^*(G')$, which go through G' once:

$$y_{i,j} = \sum_{p \in P_{G'}^*(i,j;G)} \bar{x}_p.$$

We also put $y_{ii} = 0$. Consider the matrix $Y = (y_{ij})_{i,j \in V}$. Clearly Y is symmetric, $y_{ij} \geq 0$ and $y_{ii} = 0$ for all i so we can consider Y as a traffic matrix for the undirected traffic corresponding to the subgraph G' .

If i and j are not outer nodes of V' then $P_{G'}^*(i, j; G)$ coincides with $P^*(i, j; G')$, hence the boundary conditions $y_{i,j}$ coincides with traffic demands t_{ij} . If i is an outer node and j is not an outer node, then $y_{i,j}$ is the total flow on the paths $p = (v, \dots, i, \dots, j)$, which go from either end-nodes v outside G' or i through G' once to j . If both i and j are outer nodes, then $y_{i,j}$ is the total flow, on the paths $p = (v, \dots, i, \dots, j, \dots, u)$, which go once through G' . (Here either $v \notin V'$ or $v = i$ and either $u \notin V'$ or $u = j$.)

The matrix Y depends on a traffic matrix T , subgraph G' and a flow (\bar{x}_p) . We can consider a procedure suggested in Section IV and calculate the number $\lambda(Y, U)$ for the given matrix Y . Since V' is smaller than V , the calculation of $\lambda(Y, U)$ is simpler than the calculation of $\lambda(T, U)$.

9. Conclusions. We have discussed some issues related to lifetime measures for telecommunication networks. Such measures are important for comparing networks. A lifetime measure should take into account not only the expected growth in demand but also unexpected traffic growth.

We demonstrated some advantages and disadvantages of the topology lifetime measure that was introduced in the pioneering paper [4]. In particular, we showed that this measure is based on strong enough hypotheses. We introduced a more realistic lifetime measure and discussed its properties.

Lifetime measures depend not only on the topology of the network but also on the set of working paths. Sometimes this set should be extended (for example, we need to extend this set in order to support the traffic for the time that is needed for installations of new facilities). It is convenient to use special measure for comparing paths in order to choose new working paths. We suggest a possible measure (the order of a path) for comparing paths and discuss its properties.

We show that forecasts of growth of population and migration flows can be used in the definition of lifetime measures.

Different parts of the network have a different influence on the lifetime measure, so it is important to examine the restriction of a given traffic to some parts of the network. We suggest an approach to such an examination.

Acknowledgements. We would like to thank the referees very much for their valuable comments and suggestions.

REFERENCES

- [1] Z. Dzalilov , I. Ouveysi and A. Rubinov, *Dynamic Reconfiguration of Telecommunication Networks*, Proceeding of Industrial Optimisation Symposium, Curtin University of Technology, Perth, Australia, (2003).
- [2] Z. Dzalilov, *Models of Reproduction and Exchange Defined on a Graph*, Mathematical models of economic dynamics, Vilnius, (1989), 46–57.
- [3] M. Gryseels , L. Sorbello and P. Demeester, *Planning in Uncertain and Dynamic Environments*, Proc. 9th International Network Planning Symposium, Toronto, Canada, (2000).
- [4] N. Maxemchuk , I. Ouveysi and M. Zukerman, *A quantitative measure for comparison between topologies of modern telecommunications networks*, Proceedings of IEEE GLOBECOM 2000, **1** (2000), 690–694.
- [5] N. Maxemchuk , I. Ouveysi and M. Zukerman, *A Quantitative Measure for Telecommunications Networks Topology Design*, IEEE/ACM Transactions on Networking, **13** (2005), 731–742.
- [6] I. Ouveysi and A. Wirth, *Fast Heuristics for Protection Networks for Dynamic Routing*, Journal of the Operational Research Society, **50** (1999), 262–267.
- [7] I. Ouveysi and A. Wirth, *On Design of a Survivable Network Architecture for Dynamic Routing: Optimal Solution Strategy and an Efficient Heuristic*, European Journal of Operational Research, **117** (1999), 30–44.
- [8] K.J. Patel, Z. Dzalilov, *Dynamic Reconfiguration and Graph Theory Approaches to Failures in IT based Telecommunication Networks*, Publications of the 4th IASTED International Conference on Modelling, Simulation, and Optimization (MSO), Kauai, Hawaii, USA, (2004).
- [9] K.J. Patel, Z. Dzalilov, *Dynamic reconfiguration and Systems Theory Approaches for Failures in IT based Telecommunication Networks*, Publications of the 4th IASTED International Conference on Modelling, Simulation, and Optimization (MSO), Kauai, Hawaii, USA, (2004).
- [10] M. Pickavet and P. Demeester, *Multi-Period Planning of Survivable WDM Networks*, European Transaction on Telecommunication, Special Issue on WDM NetworksName of the journal, **11** (2000), 7–16.
- [11] S. Rajogopalan , M. Singh and T. Morton, *Capacity Expansion and Replacement in Growing Markets with Uncertain Technological Breakthroughs*, Management Science, **44** (1998), 12–30.
- [12] R.L. Sheu, M.J. Ting and I.L. Wang, *Maximum flow problem in the distribution network*, Journal of Industrial and Management Optimization(JIMO), **2** (2006), 237–254.
- [13] G. Xue, W. Zhang, T. Wang and K. Thulasiraman, *On the partial path protection scheme for WDM optical networks and polynomial time computability of primary and secondary paths*, Journal of Industrial and Management Optimization(JIMO), **3** (2007), 625–643.

Received date is June 2007 and Revised dates are November 2007 and December 2007.

E-mail address: z.dzalilov@ballarat.edu.au

E-mail address: iradjouveysi@yahoo.co.uk